

L SERIES



hansaequipment.com.au

 **HANSA**
PRECISION EQUIPMENT

L SERIES

Features and Benefits



WEIGHT DISTRIBUTION

The Hansa L series features a unique connection that allows the spreader to sit much closer to the tractor aiding in weight distribution and essentially allowing larger payloads to be carried with less front weight on the tractor.



BUILT FOR THE LONGHAUL

The one piece stainless steel body is integrated with its frame, eliminating the chance of corrosion and extending the overall life of the spreader unit.



SPREAD IT ALL

The unique design of the Hansa L series uses a conveyor to deliver the product to the spinners, a lot of R&D has gone into the bin shape to ensure that bridging does not occur with the wide range of products the unit is able to spread, ranging from urea to lime.



ISOBUS

Simply Plug and play, the Hansa ISOBUS control system is compatible with all ISOBUS compliant terminals and is variable rate ready as standard. This allows the operator to move the spreader from one machine to another with ease and no setup changes.



Inclusions & Options

Inclusions ●
Optional ○

TARP	900 gsm rollover tarp	○
RATE CONTROLLER	ISOBUS Hansa H5 controller (5" Touch screen) Hansa H7 controller (7" Touch screen)	○ ○ ○
SECTION CONTROL	Twin conveyor for headland and section control (available with H7 & ISOBUS)	○
MUDGUARDS	Detachable 2 ply	○

A full range of options are available upon request

Specifications



MAX PAYLOAD
8,000 kg



SPREAD WIDTH
Urea 36m / SSP 50m

L2	L2.5	L3
CAPACITY		
2,000L	2,500L	3,000L
LOADING HEIGHT		
1,680mm	1,750mm	1,850mm
UREA CAPACITY		
1,500kg	1,800kg	2,250kg
LIME CAPACITY		
2,500kg	3,200kg	4,000kg
L4	L5	L6
CAPACITY		
4,000L	5,000L	6,000L
LOADING HEIGHT		
2,000mm	2,150mm	2,300mm
UREA CAPACITY		
3,000kg	3,750kg	4,500kg
LIME CAPACITY		
5,000kg	6,000kg	7,500kg

BIN LENGTH

1,700mm

OVERALL LENGTH

2,300mm

BIN WIDTH

2,800mm

CONVEYER WIDTH

750mm wide

OIL FLOW

80L/min

WARRANTY

12 months

Hansa provides all information in good faith, and reserves all rights to alter/change specifications without notice. Purchasers must conduct their own enquiries to ensure that the products are suitable for their own particular purposes as all information is provided as an approximation and are to be used as a guide only. Photographs may show aftermarket or optional equipment that is available at extra cost. Hansa Precision Equipment Pty Ltd. Copyright 2020. ABN: 74 604 073 350

139 Learmonth St, Alfredton VIC
sales@hansaequipment.com.au
hansaequipment.com.au



T23



hansaequipment.com.au

 **HANSA**
PRECISION EQUIPMENT

T23

Features and Benefits




BUILT FOR DURABILITY

Manufactured from 304 stainless steel, the T23 is built for durability. A grit blasted and 2 pack painted chassis ensures longevity and that return on investment of the T23 outperforms expectations.



BUILT FOR COMFORT

The T23 is built for comfort and ease of use, with hydraulic drawbar suspension for the best ride possible as standard and the option of an automatic door eliminating any need to get out to adjust settings meaning a long days spreading becomes a pleasure.



PERFORMANCE AND RELIABILITY

The reliable design of the Southern Spreaders 760 chain conveyor feeds the spinners to produce a positive and consistent product feed of all materials in all conditions and terrain.



ISOBUS

Simply Plug and play, the Hanza ISOBUS control system is compatible with all ISOBUS compliant terminals and is variable rate ready as standard. This allows the operator to move the spreader from one machine to another with ease and no setup changes.



Inclusions & Options

Inclusions ●
Optional ○

TYRES	650/65 R30.5 floatation tyres	●
	650/65 R30.5 twin radial high speed, high load floatation tyre	○
	650/60 R34 Michelin MACHXBIB IF tractor tyre	○
TARP	900 gsm rollover tarp	○
LOAD CELLS	When selected with ISOBUS rate controller auto rate control is enabled	○
RATE CONTROLLER	ISOBUS (auto rate calibration)	○
	Hansa H7 controller (7" Touch screen)	○
SECTION CONTROL	Twin conveyor for headland and section control (available with H7 & ISOBUS rate controllers)	○
AXLE	Tandem 150mm Square Axle Beam, with Rear Steerable Axle	●
BRAKES	Hydraulic	○

A full range of options are available upon request

Specifications

 **MAX PAYLOAD**
24,000 kg

 **SPREAD WIDTH**
Urea 36m / SSP 50m

CAPACITY

WATER LINE	FERTILISER	LIME
18,000L	20,000L	23,500L

TARE WEIGHT
7,300kg

LOADING HEIGHT
3,100mm

UREA CAPACITY
15,000kg

LIME CAPACITY
24,000kg

BIN LENGTH
5,950mm

OVERALL LENGTH
8,900mm

BIN WIDTH
2,700mm

STANDARD WHEEL TRACK
3,000mm

CONVEYER WIDTH
750mm wide

OIL FLOW
160L/min

WARRANTY
12 months

Hansa provides all information in good faith, and reserves all rights to alter/change specifications without notice. Purchasers must conduct their own enquiries to ensure that the products are suitable for their own particular purposes as all information is provided as an approximation and are to be used as a guide only. Photographs may show aftermarket or optional equipment that is available at extra cost. Hansa Precision Equipment Pty Ltd. Copyright 2022. ABN: 74 604 073 350

139 Learmonth St, Alfredton VIC
sales@hansaequipment.com.au
hansaequipment.com.au



T3/T4/T5



hansaequipment.com.au

 **HANSA**
PRECISION EQUIPMENT

T3/T4/T5

Features and Benefits




BUILT FOR DURABILITY

Manufactured from 304 stainless steel, the T4 is built for durability. A grit blasted and 2 pack painted chassis ensures longevity of the chassis and gives an outstanding appearance.



MAXIMUM UPTIME

Quality Permco hydraulic spinner motors and 2000 series conveyor motor drive the productivity and simplicity of this machine. Hydraulic drive translates to more flexibility and reliability thanks to less moving parts allowing the operator to get on with the job.



PERFORMANCE AND RELIABILITY

The reliable design of the Southern Spreaders 760 chain conveyor feeds the spinners to produce positive and consistent product feed of all materials in all conditions, while the simplicity renders to less maintenance.



EASE OF USE

The Hanza H5 controller does all the work, simply enter the desired rate, bout width and spinner speed from the comfort of your cab and let the computer do the rest, say goodbye to the ways of jockey wheels, complicated charts and guess work.



Inclusions & Options

Inclusions ●
Optional ○

TYRES	12.5/80-18 Industrial tyres 550/60 22.5 Flotation tyres	● ○
TARP	900 grade rollover	○
LOAD CELLS	When selected with ISOBUS rate controller auto rate calibration is enabled	○
RATE CONTROLLER	HANSA H5 controller (5" Touch screen) ISOBUS (auto rate calibration) HANSA H7 controller (7" Touch screen)	● ○ ○
SECTION CONTROL	Twin conveyor for headland and section control (available with H7 & ISOBUS rate controllers)	○
SIDE DELIVERY CONVEYOR	Single or dual delivery	○
AXLE	Single Series 80 BPW 8/285 (track options of 1600 or 1800mm)	●

A full range of options are available upon request

Specifications



MAX PAYLOAD
5500 kg



SPREAD WIDTH
Urea 24m / SSP 30m

T3	T4	T5
CAPACITY		
3,000L	4,000L	5,000L
TARE WEIGHT		
1,680kg	1,740kg	1,800kg
LOADING HEIGHT		
1,810mm	1,980mm	2,150mm
UREA CAPACITY		
2,250kg	3,000kg	3,750kg
LIME CAPACITY		
4,000kg	5,000kg	5,500kg

BIN LENGTH
2,950mm

OVERALL LENGTH
5,150mm

BIN WIDTH
1,800mm

STANDARD WHEEL TRACK
1,600mm

CONVEYER WIDTH
750mm wide

OIL FLOW
40L/min

WARRANTY
3 years

Hansa provides all information in good faith, and reserves all rights to alter/change specifications without notice. Purchasers must conduct their own enquiries to ensure that the products are suitable for their own particular purposes as all information is provided as an approximation and are to be used as a guide only. Photographs may show aftermarket or optional equipment that is available at extra cost. Hansa Precision Equipment Pty Ltd. Copyright 2020. ABN: 74 604 073 350

139 Learmonth St, Alfredton VIC
sales@hansaequipment.com.au
hansaequipment.com.au



T6



hansaequipment.com.au

 **HANSA**
PRECISION EQUIPMENT

T6

Features and Benefits



BUILT FOR DURABILITY

Manufactured from 304 stainless steel, the T6 is built for durability. A grit blasted and 2 pack painted chassis ensures longevity and that return on investment of the T6 outperforms expectations.



MAXIMUM UPTIME

The full hydraulic drive system featuring quality Permco Spinner motors and 2000 series conveyor motor means simply plugging in and going to work. Minimal grease points and required maintenance translates to simply getting on with the job.



PERFORMANCE AND RELIABILITY

The reliable design of the Southern Spreaders 760 chain conveyor feeds the spinners to produce a positive and consistent product feed of all materials in all conditions and terrain.



ISOBUS

Simply Plug and play, the Hanza ISOBUS control system is compatible with all ISOBUS compliant terminals and is variable rate ready as standard. This allows the operator to move the spreader from one machine to another with ease and no setup changes.



Inclusions & Options

Inclusions ●
Optional ○

TYRES	Harvest 18.4/30 R1 tractor tyres	●
	Harvest 600/60 R26.5 floatation tyre	○
	Michelin 600/55 R30.5 CargoBib floatation tyre	○
TARP	900 gsm rollover tarp	○
LOAD CELLS	When selected with load ISOBUS rate controller auto dynamic calibration is enabled	○
RATE CONTROLLER	ISOBUS (auto rate calibration)	○
	Hansa H5 controller (5" Touch screen)	○
	Hansa H7 controller (7" Touch screen)	○
SECTION CONTROL	Twin conveyor for headland and section control (available with H7 & ISOBUS rate controllers)	○
AXLE	Single series 100 ADR 10/335 (track options of 1,600mm, 1,800mm, 2,000mm, 2,200mm & 3,000mm)	●
BRAKES	Hydraulic	○

A full range of options are available upon request

Specifications



MAX PAYLOAD
8,000 kg



SPREAD WIDTH
Urea 36m / SSP 58m

CAPACITY
6,000L

TARE WEIGHT
2,250kg

LOADING HEIGHT
2,340mm

UREA CAPACITY
4,500kg

LIME CAPACITY
8,000kg

BIN LENGTH
3,400mm

OVERALL LENGTH
6,020mm

BIN WIDTH
2,300mm

STANDARD WHEEL TRACK
1,800mm

CONVEYER WIDTH
750mm wide

OIL FLOW
80L/min

WARRANTY
12 months

Hansa provides all information in good faith, and reserves all rights to alter/change specifications without notice. Purchasers must conduct their own enquiries to ensure that the products are suitable for their own particular purposes as all information is provided as an approximation and are to be used as a guide only. Photographs may show aftermarket or optional equipment that is available at extra cost. Hansa Precision Equipment Pty Ltd. Copyright 2022. ABN: 74 604 073 350

139 Learmonth St, Alfredton VIC
sales@hansaequipment.com.au
hansaequipment.com.au



T8



hansaequipment.com.au

HANSA
PRECISION EQUIPMENT

T8

Features and Benefits




BUILT FOR DURABILITY

Manufactured from 304 stainless steel, the T8 is built for durability. A grit blasted and 2 pack painted chassis ensures longevity and that return on investment of the T8 outperforms expectations.



MAXIMUM UPTIME

The full hydraulic drive system featuring quality Permco Spinner motors and 2000 series conveyor motor means simply plugging in and going to work. Minimal grease points and required maintenance translates to simply getting on with the job.



PERFORMANCE AND RELIABILITY

The reliable design of the Southern Spreaders 760 chain conveyor feeds the spinners to produce a positive and consistent product feed of all materials in all conditions and terrain.



ISOBUS

Simply Plug and play, the Hansa ISOBUS control system is compatible with all ISOBUS compliant terminals and is variable rate ready as standard. This allows the operator to move the spreader from one machine to another with ease and no setup changes.



Inclusions & Options

Inclusions ●
Optional ○

TYRES	Harvest 23.1/26 R1 tractor tyres	●
	Harvest 600/60 R26.5 floatation tyre	○
	Michelin 600/55 R30.5 CargoBib floatation tyre	○
TARP	900 gsm rollover tarp	○
LOAD CELLS	When selected with ISOBUS rate controller auto rate control is enabled	○
RATE CONTROLLER	ISOBUS (auto rate calibration)	○
	Hansa H5 controller (5" Touch screen)	○
	Hansa H7 controller (7" Touch screen)	○
SECTION CONTROL	Twin conveyor for headland and section control (available with H7 & ISOBUS rate controllers)	○
AXLE	Single series 100 ADR 10/335 (track options of 1,600mm, 1,800mm, 2,000mm, 2,200mm & 3,000mm)	●
BRAKES	Hydraulic	○

A full range of options are available upon request

Specifications



MAX PAYLOAD
10,000 kg



SPREAD WIDTH
Urea 36m / SSP 50m

CAPACITY
8,000L

TARE WEIGHT
2,450kg

LOADING HEIGHT
2,450mm

UREA CAPACITY
6,000kg

LIME CAPACITY
10,000kg

BIN LENGTH
3,800mm

OVERALL LENGTH
6,350mm

BIN WIDTH
2,300mm

STANDARD WHEEL TRACK
1,800mm

CONVEYER WIDTH
750mm wide

OIL FLOW
95L/min

WARRANTY
2 years

Hansa provides all information in good faith, and reserves all rights to alter/change specifications without notice. Purchasers must conduct their own enquiries to ensure that the products are suitable for their own particular purposes as all information is provided as an approximation and are to be used as a guide only. Photographs may show aftermarket or optional equipment that is available at extra cost. Hansa Precision Equipment Pty Ltd. Copyright 2020. ABN: 74 604 073 350

139 Learmonth St, Alfredton VIC
sales@hansaequipment.com.au
hansaequipment.com.au



T10



hansaequipment.com.au

 **HANSA**
PRECISION EQUIPMENT

T10

Features and Benefits




BUILT FOR DURABILITY

Manufactured from 304 stainless steel, the T10 is built for durability. A grit blasted and 2 pack painted chassis ensures longevity and that return on investment of the T10 outperforms expectations.



BUILT FOR COMFORT

The T10 is built for comfort and ease of use, with a rubber cushioned drawbar suspension as standard and the option of an automatic door eliminating any need to get out to adjust settings meaning a long days spreading becomes a pleasure.



PERFORMANCE AND RELIABILITY

The reliable design of the Southern Spreaders 760 chain conveyor feeds the spinners to produce a positive and consistent product feed of all materials in all conditions and terrain.



ISOBUS

Simply Plug and play, the Hansa ISOBUS control system is compatible with all ISOBUS compliant terminals and is variable rate ready as standard. This allows the operator to move the spreader from one machine to another with ease and no setup changes.



Inclusions & Options

Inclusions ●
Optional ○

TYRES	Harvest 23.1/26 Trojan tyres	●
	Michelin or Harvest 650/65 R30.5 tyres	○
	Harvest 650/65 R42 HR45 R1 tyres	○
	Mitas 480/80 R34 tyres	○
TARP	900 gsm rollover tarp	○
LOAD CELLS	When selected with ISOBUS rate controller auto rate control is enabled	○
RATE CONTROLLER	ISOBUS (auto rate calibration)	○
	Hansa H7 controller (7" Touch screen)	○
SECTION CONTROL	Twin conveyor for headland and section control (available with H7 & ISOBUS rate controllers)	○
AXLE	Single series 150 ADR 10/335 (track options of 2,000mm, 2,200mm & 3,000mm)	●
BRAKES	Hydraulic	○

A full range of options are available upon request

Specifications

 **MAX PAYLOAD**
12,000 kg

 **SPREAD WIDTH**
Urea 36m / SSP 50m

CAPACITY
9,500L

TARE WEIGHT
4,150kg

LOADING HEIGHT
2,800mm

UREA CAPACITY
7,000kg

LIME CAPACITY
12,000kg

BIN LENGTH
4,000mm

OVERALL LENGTH
6,850mm

BIN WIDTH
2,300mm

STANDARD WHEEL TRACK
2,000mm

CONVEYER WIDTH
750mm wide

OIL FLOW
130L/min

WARRANTY
12 months

Hansa provides all information in good faith, and reserves all rights to alter/change specifications without notice. Purchasers must conduct their own enquiries to ensure that the products are suitable for their own particular purposes as all information is provided as an approximation and are to be used as a guide only. Photographs may show aftermarket or optional equipment that is available at extra cost. Hansa Precision Equipment Pty Ltd. Copyright 2020. ABN: 74 604 073 350

139 Learmonth St, Alfredton VIC
sales@hansaequipment.com.au
hansaequipment.com.au



T12



hansaequipment.com.au

 **HANSA**
PRECISION EQUIPMENT

T12

Features and Benefits




BUILT FOR DURABILITY

Manufactured from 304 stainless steel, the T12 is built for durability. A grit blasted and 2 pack painted chassis ensures longevity and that return on investment of the T12 outperforms expectations.



BUILT FOR COMFORT

The T12 is built for comfort and ease of use, with hydraulic drawbar suspension for the best ride possible as standard and the option of an automatic door eliminating any need to get out to adjust settings meaning a long days spreading becomes a pleasure.



PERFORMANCE AND RELIABILITY

The reliable design of the Southern Spreaders 760 chain conveyor feeds the spinners to produce a positive and consistent product feed of all materials in all conditions and terrain.



ISOBUS

Simply Plug and play, the Hanza ISOBUS control system is compatible with all ISOBUS compliant terminals and is variable rate ready as standard. This allows the operator to move the spreader from one machine to another with ease and no setup changes.



Inclusions & Options

Inclusions ●
Optional ○

TYRES	650/65 R30.5 floatation tyres	●
	520/85 R38 high load, high speed R1 tractor tyre	○
	650/65 R30.5 twin radial high speed, high load flotation tyre	○
TARP	900 gsm rollover tarp	○
LOAD CELLS	When selected with ISOBUS rate controller auto rate control is enabled	○
RATE CONTROLLER	ISOBUS (auto rate calibration) Hansa H7 controller (7" Touch screen)	○
SECTION CONTROL	Twin conveyor for headland and section control (available with H7 & ISOBUS rate controllers)	○
AXLE	Single series 150 ADR 10/335 (track options of 2,000mm, 2,200mm, 2,500mm & 3,000mm)	●
BRAKES	Hydraulic	○

A full range of options are available upon request

Specifications

 **MAX PAYLOAD**
14,000 kg

 **SPREAD WIDTH**
Urea 36m / SSP 50m

CAPACITY
11,000L

TARE WEIGHT
4,450kg

LOADING HEIGHT
2,950mm

UREA CAPACITY
8,250kg

LIME CAPACITY
14,000kg

BIN LENGTH
4,000mm

OVERALL LENGTH
6,850mm

BIN WIDTH
2,300mm

STANDARD WHEEL TRACK
2,000mm

CONVEYER WIDTH
750mm wide

OIL FLOW
130L/min

WARRANTY
12 months

Hansa provides all information in good faith, and reserves all rights to alter/change specifications without notice. Purchasers must conduct their own enquiries to ensure that the products are suitable for their own particular purposes as all information is provided as an approximation and are to be used as a guide only. Photographs may show aftermarket or optional equipment that is available at extra cost. Hansa Precision Equipment Pty Ltd. Copyright 2020. ABN: 74 604 073 350

139 Learmonth St, Alfredton VIC
sales@hansaequipment.com.au
hansaequipment.com.au



T15



hansaequipment.com.au

 **HANSA**
PRECISION EQUIPMENT

T15

Features and Benefits



BUILT FOR DURABILITY

Manufactured from 304 stainless steel, the T15 is built for durability. A grit blasted and 2 pack painted chassis ensures longevity and that return on investment of the T15 outperforms expectations.



BUILT FOR COMFORT

The T15 is built for comfort and ease of use, with hydraulic drawbar suspension for the best ride possible as standard and the option of an automatic door eliminating any need to get out to adjust settings meaning a long days spreading becomes a pleasure.



PERFORMANCE AND RELIABILITY

The reliable design of the Southern Spreaders 760 chain conveyor feeds the spinners to produce a positive and consistent product feed of all materials in all conditions and terrain.



ISOBUS

Simply Plug and play, the Hansa ISOBUS control system is compatible with all ISOBUS compliant terminals and is variable rate ready as standard. This allows the operator to move the spreader from one machine to another with ease and no setup changes.



Inclusions & Options

Inclusions ●
Optional ○

TYRES	Alliance 331 600/60 R30.5 floatation tyre	○
	Harvest 600/65 R28 tractor tyre	●
	Michelin VF CFO+ 520/80 R26 tractor tyre	○
	Michelin CARGOXBIB 650/60 R30.5 floatation tyre	○
	Michelin MACHXBIB 600/70 R28 tractor tyre	○
TARP	900 gsm rollover tarp	○
LOAD CELLS	When selected with load ISOBUS rate controller auto dynamic calibration is enabled	○
RATE CONTROLLER	ISOBUS (auto rate calibration)	○
	Hansa H7 controller (7" Touch screen)	○
SECTION CONTROL	Twin conveyor for headland and section control (available with H7 & ISOBUS rate controllers)	○
AXLE	Tandem 150mm Square Axle Beam, with Rear Steerable Axle (track options of 2,500mm & 3,000mm)	●
BRAKES	Hydraulic	○

A full range of options are available upon request

Specifications



MAX PAYLOAD
20,000 kg



SPREAD WIDTH
Urea 36m / SSP 50m

CAPACITY
14,000L

TARE WEIGHT
6,200kg

LOADING HEIGHT
3,000mm

UREA CAPACITY
11,000kg

LIME CAPACITY
18,000kg

BIN LENGTH
5,100mm

OVERALL LENGTH
7,900mm

BIN WIDTH
2,400mm

STANDARD WHEEL TRACK
2,400mm

CONVEYER WIDTH
750mm wide

OIL FLOW
140L/min

WARRANTY
12 months

Hansa provides all information in good faith, and reserves all rights to alter/change specifications without notice. Purchasers must conduct their own enquiries to ensure that the products are suitable for their own particular purposes as all information is provided as an approximation and are to be used as a guide only. Photographs may show aftermarket or optional equipment that is available at extra cost. Hansa Precision Equipment Pty Ltd. Copyright 2021. ABN: 74 604 073 350

139 Learmonth St, Alfredton VIC
sales@hansaequipment.com.au
hansaequipment.com.au

